



Application: They are suitable for oxidant gas suction, installation in corrosive environments such as chemical industries, laboratories, biological wastewater treatment, underground and outdoors etc.

Corrosion Proof Single Inlet Plastic Roof Fans High Pressure

- Completely made of **Polypropylene**.
- Polypropylene Centrifugal impeller with forward curve blades.
- The material and design make the fan corrosion and spark proof.
- High quality electric motors, **IP 55, Class F**.
- For speed controllers see pages 320-322.
- **Performance curves for all fans.**



1400 RPM

Type	Power HP	Inlet Flange \varnothing mm	Air flow m ³ /h	Static Pressure mm H ₂ O	Noise Level dB (A)	Price
PLAST - 16/4 -OP - HP	0,25	160	400	26	60	⌘
PLAST - 16B/4 -OP - HP	0,50	160	800	41	63	⌘
PLAST - 20/4 -OP - HP	1,00	160	1.450	56	69	⌘

2800 RPM

Type	Power HP	Inlet Flange \varnothing mm	Air flow m ³ /h	Static Pressure mm H ₂ O	Noise Level dB (A)	Price
PLAST - 16/2 --OP - HP	1,00	160	800	105	67	⌘
PLAST - 16B/2 -OP - HP	2,00	160	1.500	170	72	⌘
PLAST - 20/2 -OP - HP	4,00	160	2.300	250	80	⌘

