











Applications: Shopping centers, small shops, banks, hospitality, schools, office buildings, public buildings.

Heat Recovery Units ARUMAK LP Series

- Medium-high efficiency heat recovery unit (Eff.78%). Low profile with electronic regulation and AC motor for optimized management. Counter flow heat exchanger, Eurovent certified. Set in insulated steel boxes with sandwich polyurethane foam panels. With partial bypass and regulation control CTRL-F and CTRL-DPH.
- With F7/F7 or F7+F9/F7 filters.
- Horizontal and false ceiling installation version.
- Modular structure made of extruded aluminium profiles and double skin Aluzinc. Made up of sandwich panels with injected polyurethane foam insulation, thickness 25 mm and density 42 kg/m³.
- Aluminium Counter flow heat exchanger with 78% efficiency.
- Centrifugal fans with direct motor coupled with double suction according to ErP 2018.

Control:

CTRL-F: 4 speeds, ON / OFF bypass, 3 temperatures and indication of filter failure. Optional: portable display with connection cables.

CTRL-DPH: manual speed, manages bypass auto- matically. Regulation of fresh air, fault detection and time programming.

Under Request:


Without control.


Manual bypass.


F9/F7 filters.

CTRL-MAX2 with Modbus RTU protocol.

| Technical Characteristics ARUMAK LP Series | | | | | | | | |
|--|---------------|-------|--------------------|-----------------|----------------|----------|--|--|
| Туре | Power (kW) | RPM | Air Flow (m³/h) | Sound db (A) | Weight (Kg) | Price | | |
| ARUMAK LP 470 | 2x0.15 | 1.030 | 470 | 35 | 74 | a | | |
| ARUMAK LP 850 | 2x0.29 | 1.600 | 850 | 46 | 91 | a | | |
| ARUMAK LP 1750 | 2x0.40 | 1.372 | 1.750 | 53 | 142 | a | | |
| ARUMAK LP 2100 | 2x0.40 | 1.372 | 2.100 | 49 | 150 | a | | |
| ARUMAK LP 2900 | 2x0.55 | 1.289 | 2.900 | 50 | 273 | a | | |
| ARUMAK LP 4200 | 2x0.75 | 1.404 | 4.200 | 57 | 291 | <u> </u> | | |









| Dimensions ARUMAK LP Series (470-2100) | | | | | | | | |
|--|-----|------|------|-----|-----|--|--|--|
| Туре | Α | В | С | E | F | | | |
| ARUMAK LP 470 | 370 | 1100 | 1050 | 185 | 200 | | | |
| ARUMAK LP 850 | 430 | 1200 | 1150 | 215 | 250 | | | |
| ARUMAK LP 1750 | 500 | 1460 | 1300 | 283 | 315 | | | |
| ARUMAK LP 2100 | 550 | 1460 | 1300 | 283 | 315 | | | |









| Dimensions ARUMAK LP Series (2900-4200) | | | | | | | | |
|---|-----|------|------|-----|-----|-----|-----|--|
| Туре | Α | В | С | E | F | G | Ø | |
| ARUMAK LP 2900 | 640 | 2300 | 1500 | 327 | 350 | 290 | 400 | |
| ARUMAK LP 4200 | 640 | 2300 | 1980 | 327 | 350 | 290 | 400 | |

