



Optional:

- Filter.
- Vertical mount.
- Door switch.
- Inox body (430 stainless steel).



Simple 2 Speed Air Curtains

- Easy installation.
- Adjustable air direction.
- Overall automation and operating safety.
- Low noise level.
- Energy saving.
- Keeps out dust, insects, odors, pollution and moisture.

Suitable for banks, bars, hospitals, stores, hotels, cafes, health centers, surgeries, hairdressers etc.

Low Air Flow For Door Height Up To 2.50m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
A-11W ή Δ-11W	0,70	847	120	45 / 54	4	800 / 1000	8,0 / 10,0	€ 412,00
A-12W ή Δ-12W	0,80	945	120	45 / 54	4	900 / 1150	8,0 / 10,0	€ 422,00
A-13W ή Δ-13W	1,00	1.045	120	45 / 54	4	1050 / 1300	8,0 / 10,0	€ 438,00
K-14W	1,20	1.206	240	53 / 60	4	1100 / 1400	8,0 / 10,0	€ 577,00
K-15W	1,40	1.406	240	53 / 60	4	1350 / 1700	8,0 / 10,0	€ 606,00
K-16W	1,60	1.606	240	53 / 60	4	1600 / 2000	8,0 / 10,0	€ 636,00
K-17W	1,80	1.806	240	55 / 61	4	1800 / 2200	8,0 / 10,0	€ 648,00
K-18W	2,00	2.006	240	55 / 61	4	2000 / 2500	8,0 / 10,0	€ 679,00

Medium Air Flow For Door Height Up To 4.00m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
A-33W ή Δ-33W	1,00	1149	350	62 / 63	8	2125 / 2510	11,0 / 13,0	€ 549,00
K-34W	1,20	1242	350	64 / 66	8	2370 / 2800	11,0 / 13,0	€ 648,00
K-35W	1,40	1442	660	64 / 66	12	2850 / 3370	11,0 / 13,0	€ 689,00
K-36W	1,60	1642	660	64 / 66	12	3330 / 3930	11,0 / 13,0	€ 730,00
K-37W	1,80	1842	660	64 / 67	12	3800 / 4500	11,0 / 13,0	€ 789,00
K-38W	2,00	2042	660	64 / 67	12	4285 / 5065	11,0 / 13,0	€ 825,00

High Air Flow For Door Height Up To 6.00m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
A-22 ή Δ-22	1,00	1270	660	65 / 68	12	2615 / 3050	12,0 / 14,0	€ 703,00
A-23 ή Δ-23	1,20	1491	660	65 / 68	12	3185 / 3715	12,0 / 14,0	€ 747,00
K-24	1,20	1259	660	65 / 68	12	2600 / 3035	12,0 / 14,0	€ 762,00
K-26	1,60	1663	660	65 / 68	12	3640 / 4245	12,0 / 14,0	€ 889,00
K-28	2,00	2097	660	65 / 68	15	5280 / 5580	12,0 / 14,0	€ 1.013,00

- L stands for left motor
- R stands for right motor.
- C stands for centered motor
- Filter according to type, upon request.

Simple Air Curtains Controls	Price
Wired remote control upon request.	€ 75,00
Wireless remote control upon request.	€ 34,00

- Simple air curtains are supplied with a standard built in two-speed control.
- Wired or wireless remote control upon request.

Simple 2 Speed Air Curtains

2 Speed Air Curtains

Type	Maximum Length(m)	Width (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet height h (mm)	Weight (kgr)
A-11W ή Δ-11W	847	166	172	700	54	64	8,00
A-12W ή Δ-12W	945	166	172	800	54	64	9,50
A-13W ή Δ-13W	1045	166	172	900	54	64	11,00
K-14W	1206	166	172	1160	54	64	15,00
K-15W	1406	166	172	1360	54	64	17,00
K-16W	1606	166	172	1560	54	64	19,00
K-17W	1806	166	172	1760	54	64	22,00
K-18W	2006	166	172	1960	54	64	24,00

Medium Air Flow For Door Height Up To 4.00m

Type	Maximum Length(m)	Width (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet height h (mm)	Weight (kgr)
A-33W ή Δ-33W	1149	212	205	900	76	64	19,00
K-34W	1242	212	205	1199	76	64	22,00
K-35W	1442	212	205	1400	76	64	24,00
K-36W	1642	212	205	1601	76	64	26,00
K-37W	1842	212	205	1802	76	64	28,00
K-38W	2042	212	205	2003	76	64	30,00

High Air Flow For Door Height Up To 6.00m

Type	Maximum Length(m)	Width (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet height h (mm)	Weight (kgr)
A-22 ή Δ-22	1270	231	227	1015	76	64	24,00
A-23 ή Δ-23	1491	231	227	1236	76	64	27,00
K-24	1259	231	227	1200	76	64	27,00
K-26	1663	231	227	1603	76	64	31,00
K-28	2097	231	227	2044	76	64	36,00

