

Simple Recessed Air Curtains RS Series

- Energy saving Simple Recessed Air Curtains.
- Door height up to 4,00m.
- 2 Speed (HI-LOW).
- Conventional or infrared remote control.
- Modern design.
- New eco control system (ECO).
- 230V/50Hz.
- Controlled Microclimate.
- Keeps out dust, insects, odors, pollution and moisture.




Is suitable for covering openings in : Super markets, Hospitals, Hotel Lobbys, Train Stations, Department Stores, Large Fast Foods , Airports, Bus stations etc.

Simple Recessed Air Curtains RS Series

Type	Max door width (m)	Total length (mm)	Max door height (m)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (BF)	Air flow min max (m3/h)	Outlet velocity (m/sec)	Price (I.R.)
RS 34	1,20	1255	4,00	350	64/66	8	2130/2600	9,0/11,0	€ 1.094,00
RS 35	1,40	1455	4,00	660	64/66	12	2545/3110	9,0/11,0	€ 1.166,00
RS 36	1,60	1655	4,00	660	64/66	12	2960/3620	9,0/11,0	€ 1.240,00
RS 37	1,80	1855	4,00	660	64/67	12	3380/4130	9,0/11,0	€ 1.312,00
RS 38	2,00	2055	4,00	660	64/67	12	3790/4632	9,0/11,0	€ 1.386,00

Simple Recessed Air Curtains RS Series Dimensions

Type	Length L (mm)	Hanging Points K (mm)	Total Length I (mm)	Weight (Kg)
RS 34	1255	1055	1395	32,5
RS 35	1455	1255	1595	38,0
RS 36	1655	1455	1795	43,0
RS 37	1855	1655	1995	47,0
RS 38	2055	1855	2195	52,0



Cross flow impeller \varnothing 120 diameter

