

Electrically Heated Air Curtains

- **Energy saving Electrically Heated Air Curtains.**
- Creation of a hot air barrier that prevents heat losses between areas of different temperature.
- Prevents air layering especially during heating season (winter) through the circulation of great air volumes.
- Easy installation.
- Low noise level.
- Keeps out dust, insects, odors, pollution and moisture.

Operational Choices:

- Two speed operation (HI - LOW).
- NL operation.
- Wired Remote Control Operation or Infrared Remote Control Operation.
- New eco control system (ECO).



Suitable for banks, bars, hospitals, stores, hotels, cafes, health centers, surgeries, hairdressers etc.

Electrically Heated Air Curtains Low Air Flow For Door Height Up To 2.30m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
AEH-13W ή ΔEH-13W	1,00	1100	120	43 / 54	4	900 / 1150	7,0 / 9,0	€ 937,00
KEH-14W	1,20	1206	240	45 / 55	4	990 / 1280	7,0 / 9,0	€ 1.100,00
KEH-15W	1,40	1406	240	50 / 56	4	1200 / 1500	7,0 / 9,0	€ 1.175,00
KEH-16W	1,60	1606	240	50 / 56	4	1400 / 1750	7,0 / 9,0	€ 1.258,00
KEH-17W	1,80	1806	240	52 / 59	4	1600 / 2000	7,0 / 9,0	€ 1.333,00
KEH-18W	2,00	2006	240	52 / 59	4	1800 / 2300	7,0 / 9,0	€ 1.416,00

Electrically Heated Air Curtains Medium Air Flow For Door Height Up to 3.50m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
AEH-33W ή ΔEH-33W	1,00	1149	350	60 / 62	8	1930 / 2320	10,0 / 12,0	€ 1.012,00
KEH-34W	1,20	1242	350	62 / 65	8	2160 / 2590	10,0 / 12,0	€ 1.175,00
KEH-35W	1,40	1442	660	62 / 65	12	2600 / 3110	10,0 / 12,0	€ 1.258,00
KEH-36W	1,60	1642	660	62 / 65	12	3024 / 3630	10,0 / 12,0	€ 1.333,00
KEH-37W	1,80	1842	660	62 / 66	12	3460 / 4150	10,0 / 12,0	€ 1.416,00
KEH-38W	2,00	2042	660	60 / 66	12	3895 / 4675	10,0 / 12,0	€ 1.497,00

Electrically Heated Air Curtains High Air Flow For Door Height Up to 5.00m

Type	Maximum Length(m)	Width (mm)	Power (Motor) (W)	Noise Level dB (A)	Capacitor (µF)	Air flow min-max (m³/h)	Outlet Velocity min-max (m/sec)	Price
AEH-22 ή ΔEH-22	1,00	1270	660	64 / 67	12	2400 / 2830	11,0 / 13,0	€ 1.175,00
AEH-23 ή ΔEH-23	1,20	1491	660	64 / 67	12	2920 / 3450	11,0 / 13,0	€ 1.258,00
KEH-24	1,20	1259	660	64 / 67	12	2380 / 2815	11,0 / 13,0	€ 1.424,00
KEH-26	1,60	1663	660	64 / 67	12	3335 / 3940	11,0 / 13,0	€ 1.572,00
KEH-28	2,00	2097	660	64 / 67	12	4385 / 5180	11,0 / 13,0	€ 1.722,00

Electrically Heated Air Curtain Controls

	Price
Wire Remote Control (Upon Request)	€ 75,00
Wireless Remote Control (Upon Request)	€ 34,00

- All electrically heated air curtains are supplied with a standard wired remote control.
- Wireless remote control upon request.

Electrically Heated Air Curtains

Electrically Heated Air Curtains Low Air Flow For Door Height Up to 2.30m Dimensions

Type	Total length (mm)	Total width W (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet Height	Weight (Kg)	Thermal Power (kW)	Max Current Cons	T outlet-T inlet (°C)	Power Stage	Protection Rate
AEH-13W ή ΔEH-13W	1100	274	172	900	54	64	21,00	6 / 9	9 / 13,5	20-26 / 28-36	4	IP20
KEH-14W	1206	274	172	1160	54	64	24,00	9	13,5	28-36	4	IP20
KEH-15W	1406	274	172	1360	54	64	27,00	9	13,5	27-35	4	IP20
KEH-16W	1606	274	172	1560	54	64	30,00	12	18	25-33	4	IP20
KEH-17W	1806	274	172	1760	54	64	33,00	12 / 15	18 / 22,5	16-21 / 20-25	4	IP20
KEH-18W	2006	274	172	1960	54	64	37,00	12 / 15	18 / 22,5	16-21 / 20-25	4	IP20

Electrically Heated Air Curtains Medium Air Flow For Door Height Up to 3.50m Dimensions

Type	Total length (mm)	Total width W (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet Height	Weight (Kg)	Thermal Power (kW)	Max Current Cons	T outlet-T inlet (°C)	Power Stage	Protection Rate
AEH-33W ή ΔEH-33W	1149	277	205	900	76	64	28,00	9 / 12	13 / 18	18-20 / 20-34	4	IP20
KEH-34W	1242	277	205	1199	76	64	31,00	12 / 15	13,5	16-18 / 18-20	4	IP20
KEH-35W	1442	277	205	1400	76	64	34,00	12 / 15	13,5	15-17 / 17-19	4	IP20
KEH-36W	1842	277	205	1601	76	64	37,00	12 / 15	18 / 22,5	15-17 / 17-19	4	IP20
KEH-37W	2042	277	205	1802	76	64	39,00	15 / 18	9 / 13,5	15-17 / 17-19	4	IP20
KEH-38W	2042	277	205	2003	76	64	41,00	15 / 18	9 / 13,5	14-16 / 17-20	4	IP20

Electrically Heated Air Curtains High Air Flow For Door Height Up to 5.00m Dimensions

Type	Total length (mm)	Total width W (mm)	Height H (mm)	Outlet length l (mm)	Outlet width w (mm)	Outlet Height	Weight (Kg)	Thermal Power (kW)	Max Current Cons	T outlet-T inlet (°C)	Power Stage	Protection Rate
AEH-22 ή ΔEH-22	1270	306	227	1015	76	64	36,00	15 / 18	22 / 26	17-18 / 19-20	4	IP20
AEH-22 ή ΔEH-22	1491	306	227	1236	76	64	40,00	15 / 18	22 / 26	17-18 / 19-20	4	IP20
KEH-24	1259	306	227	1200	76	64	40,00	15 / 18	22 / 26	17-18 / 19-20	4	IP20
KEH-26	1663	306	227	1603	76	64	45,00	15 / 18	22 / 26	17-18 / 19-20	4	IP20
KEH-28	2097	306	227	2044	76	64	51,00	18	26	19-20	4	IP20

